



Cisco ATA 191 Analog Telephone Adapter

The Cisco ATA 191 Analog Telephone Adapter is a 2-port handset-to-Ethernet adapter that brings traditional analog telephony devices into the IP world.



Product overview

The Cisco® ATA 191 Analog Telephone Adapter turns traditional telephone, fax, and overhead paging communications devices into IP devices for greater cost-effectiveness. Customers can take advantage of IP telephony applications by connecting their analog devices to Cisco analog telephone adapters.

The Cisco ATA 191 Analog Telephone Adapter is the preferred solution to address the needs of customers who connect to enterprise networks, small offices,

or the emerging unified communications as a service from the cloud. It has two standard FXS ports, which can be configured independently as two Session Initiation Protocol (SIP) registrations. With the ATA 191, customers can protect and extend their existing investment in analog systems, as well as smooth their migration to pure voice over IP in an affordable and reliable way.

Features and benefits

Feature	Benefit
Voice quality	Offers clear, natural-sounding voice quality via advanced preprocessing, high-performance echo cancellation, Voice Activity Detection (VAD), and Comfort Noise Generation (CNG)
Security	Provides a complete security solution for both media and signaling
IPv6	Enables an IPv4/IPv6 dual stack to help migration to IPv6

The Cisco ATA 191 Analog Telephone Adapter is compatible with Cisco call control systems (CUCM, CME)

Product specifications

Feature	Specifications
Physical dimensions (H×W×D)	3.9 x 3.9 x 1 in. (100 × 100 × 28 mm)
Weight	4.7 oz (132.1 g)
Hardware	Interface: Two RJ11 FXS ports, one 10/100 Mbps RJ-45 Ethernet port Button: Reset / Problem Reporting (PRT) LED indicators: Power, Network, Phone 1, Phone 2, PRT Wall mountable
Subscriber Line Interface Circuit (SLIC)	Ring voltage: 40 to 90 Vpk configurable Ring frequency accuracy: 1% Ring waveform: Trapezoidal or sinusoidal Maximum ringer load: 3 Ringer Equivalence Numbers (RENs) On-hook voltage (tip and ring): -46 to -56V Off-hook current: 25mA +/-10% Terminating impedance: 600 ohm resistive, 900 ohm resistive, or 220 ohm + 820 ohm 120 nF complex impedance Frequency response: 300 to 3400 Hz Return loss (600 ohm, 300 to 3400 Hz): up to 26 dB Idle channel noise: <65 dBm Op Longitudinal balance: 58 dB (typical) Voice quality Mean Opinion Score (MOS): >4.0 Voice quality jitter: <150ms
Networking	IMAC address IPv4 only IPv6 only IPv4/IPv6 dual stack Session Initiation Protocol (SIP) Transmission Control Protocol (TCP) User Datagram Protocol (UDP) Real Time Protocol (RTP) Real Time Control Protocol (RTCP) HTTP Secure HTTP (HTTPS) Trivial File Transfer Protocol (TFTP) Address Resolution Protocol (ARP) DNS A and AAAA records Dynamic Host Configuration Protocol (DHCP) client

Feature	Specifications
Networking	Internet Control Message Protocol (ICMP) Simple Network Time Protocol (SNTP) Cisco Discovery Protocol (CDP) Link Layer Discovery Protocol (LLDP)
Quality of Service (QoS)	IEEE 802.1p/Q (QoS and VLAN tagging) Differentiated Services (DiffServ) / Type of Service (ToS)
Telephony	Call forwarding: No answer, busy, and all Call hold and resume Caller ID generation (name and number) Caller ID with name and number Call pickup and group pickup Call transfer Call waiting Conference Country-specific tones and cadences Disconnect tone Distinctive ringing: Calling and called number Flash hook timer
Subscriber Line Interface Circuit (SLIC)	Ring voltage: 40 to 90 Vpk configurable Ring frequency accuracy: 1% Ring waveform: Trapezoidal or sinusoidal Maximum ringer load: 3 Ringer Equivalence Numbers (RENs) On-hook voltage (tip and ring): -46 to -56V Off-hook current: 25mA +/-10% Terminating impedance: 600 ohm resistive, 900 ohm resistive, or 220 ohm + 820 ohm 120 nF complex impedance Frequency response: 300 to 3400 Hz Return loss (600 ohm, 300 to 3400 Hz): up to 26 dB Idle channel noise: <65 dBm Op Longitudinal balance: 58 dB (typical) Voice quality Mean Opinion Score (MOS): >4.0 Voice quality jitter: <150ms Hook flash event signaling Hotline and warm line calling Message Waiting Indicator (MWI) tones Music on hold Off-hook warning tone Polarity control Redial Share lines Speed dial Tip and ring voltage adjustment setting Visual Messaging Waiting Indicator (VMWI) using Frequency Shift Keying (FSK)

Feature	Specifications
Audio	Codec: G.711 a-law, G.711 μ -law, G.729a, G.729ab Full duplex audio Echo cancellation Voice activity detection Silence suppression Comfort noise generation Adaptive jitter buffer Frame loss concealment Adjustable audio frames per packet Call progress tone generation Impedance and gain adjustment Dynamic audio payload
Fax and modem	Real-time fax over IP via T.38 fax relay (Group 3) Fax pass-through via G.711 (Group 3) Fax tone detection and pass-through Auto negotiation on transmission rate
Provisioning and management	Central configuration Interactive Voice Response (IVR) Automated provisioning and upgrading via HTTP and TFTP SSH access Nonintrusive, in-service upgrades Report generation and event logging Dedicate PRT button Support RTP statistics Syslog (multilevel granularity) Dual image
Security	System reset to factory default Password-protected administrator access authority Provisioning, configuration, and authentication HTTPS with factory-installed client certificate Advanced Encryption Standard (AES) encryption SIP over Transport Layer Security (TLS) 1.1 and 1.2 Secure (encrypted) calling using Secure RTP (sRTP) Encrypted TFTP configuration files Image authentication Secure boot Secure Shell (SSH)
Power	DC input voltage: 5V DC at 2.4A maximum Power consumption: 5W Switching type (100 to 240V) automatic Power adapter: 100 to 240V and 50 to 60 Hz (26 to 34 VA) AC input, with 6-ft (1.8-m) cord
Reliability	Mean Time Between Failures (MTBF): 300,000 hours Operating temperature: 32° to 104°F (0° to 40°C) Nonoperating temperature: 14° to 140°F (-10° to 60°C) Humidity: Operating 10% to 90%, noncondensing; nonoperating 10% to 95%, noncondensing

Feature	Specifications
Compliance (regulatory)	CE markings per directives 2014/30/EU and 2014/35/EU
Compliance (safety)	UL 60950 Second Edition CAN/CSA-C22.2 No. 60950 Second Edition IEC 60950-1:2005 (Second Edition) + A1:2009 + A2:2013 and/or AS/NZS 60950.1:2015
Compliance (EMC)	AS/NZS CISPR 32:2015 Class B CISPR 32: 2015 Class B EN 55032: 2015 Class B EN 61000-3-2: 2014 Class A EN 61000-3-3: 2013 EN 55024:2010+A1: 2015 EN 61000-4-2: 2009 EN 61000-4-3: 2006+A1:2008+A2:2010 EN 61000-4-4: 2012 EN 61000-4-5: 2014 EN 61000-4-6: 2014+AC:2015 EN 61000-4-8: 2010 EN 61000-4-11: 2004 FCC Part 15, Subpart B ANSI C63.4-2014 ICES-003 Issue 6: 2016 ANSI C63.4-2014 VCCI-TECHNICAL REQUIREMENTS (VCCI-CISPR 32: 2016) / CISPR 32: 2015 class B

Warranty information

The Cisco ATA 191 Analog Telephone Adapter is covered by a 1-year limited hardware warranty.

Learn more

For additional details on the Cisco ATA 191 Analog Telephone Adapter, go to cisco.com/c/en/us/products/unified-communications/ata-190-series-analog-telephone-adapters/index

For more information, please contact a sales representative. Visit ringcentral.com or call 855-774-2510.

RingCentral, Inc. (NYSE: RNG) is a leading provider of business cloud communications and contact center solutions based on its powerful Message Video Phone™ (MVP™) global platform. More flexible and cost effective than legacy on-premises PBX and video conferencing systems that it replaces, RingCentral empowers modern mobile and distributed workforces to communicate, collaborate, and connect via any mode, any device, and any location. RingCentral offers three key products in its portfolio including RingCentral MVP™, a unified communications as a service (UCaaS) platform including team messaging, video meetings, and a cloud phone system; RingCentral Video®, the company's video meetings solution with team messaging that enables Smart Video Meetings™; and RingCentral cloud Contact Center solutions. RingCentral's open platform integrates with leading third-party business applications and enables customers to easily customize business workflows. RingCentral is headquartered in Belmont, California, and has offices around the world.



RingCentral, Inc. 20 Davis Drive, Belmont, CA 94002. ringcentral.com

© 2022 RingCentral, Inc. All rights reserved. RingCentral and the RingCentral logo are registered trademarks of RingCentral, Inc. Other third-party marks and logos displayed in this document are the trademarks of their respective owners.