

Polycom® VVX® 150

An affordable and reliable IP desk phone

The Polycom VVX 150 business IP desk phone is a high-quality, two-line IP phone that delivers reliable performance and enterprise-grade sound quality. It is ideal for home offices or shared/common areas, such as lobbies, hallways, break rooms, or any location that needs simple and reliable voice connectivity.



The industry's best audio

The VVX 150 offers both Polycom HD Voice™ and Polycom Acoustic Fence™ technologies. Together, they dramatically improve the most important component of the VVX experience—voice clarity.

HD Voice delivers superior, high-definition sound quality through industry-leading, advanced voice processing capabilities. Polycom's exclusive Polycom Acoustic Fence technology keeps business conversations free from extraneous noises, echoes, and distractions.

Easy-to-use, simple voice communications experience

The Polycom VVX 150 is a dependable business IP phone, that is intuitive for end users. The Polycom VVX 150 has a simple, practical design. Its modern, intuitive navigation makes it easy to use and requires minimal training, resulting in rapid adoption.

- Crystal clear HD audio performance, so you can hear every conversation detail
- 2.5" graphical, backlit monochrome LCD display offering visual information at a glance
- Two 10/100 Ethernet ports offer cost savings

Features and specifications

User interface features

- 2.5" graphical backlit monochrome LCD (132x64 pixel resolution)
- Voicemail support
- Reversible deskstand/wallmount
- Unicode UTF-8 character support
- Intuitive user-interface with multi-language support

Feature keys

- Four context-sensitive “soft” keys
- Two line keys with bi-color (red/green) LED “Home” feature key
- Four-way navigation key cluster with center “Select” key
- Two volume control keys
- Dedicated keys:
 - Back and Home
 - Hold and Transfer
 - Headset
 - Hands-free speakerphone
 - Microphone Mute

Audio features

- Polycom Acoustic Clarity™ technology providing full-duplex conversations, acoustic echo cancellation, and background noise suppression
- TIA-920 Wideband Audio
- Type 1 compliant (IEEE 1329 full duplex)
- Frequency response—150 Hz–7 kHz for hands-free speakerphone, handset, and optional headset mode
- Codecs: G.711 (A-law and μ -law), G.729AB, G.722 (HD Voice), iLBC
- Individual volume settings with visual feedback for each audio path
- Voice activity detection
- Comfort noise generation
- DTMF tone generation (RFC 2833 and in-band)
- Low-delay audio packet transmission
- Adaptive jitter buffers
- Packet loss concealment

Headset and handset compatibility

- Dedicated RJ-9 headset port
- Hearing aid compatibility to ITU-T P.370 and TIA 504A standards
- Compliant with ADA Section 508 Subpart B 1194.23 (all)

- Hearing aid compatible (HAC) handset for magnetic coupling to hearing aids
- Compatible with commercially available TTY adapter equipment

Call handling features

- One SIP identity (registration)
- Additional programmable line key
- Call timer and call waiting
- Call transfer, hold, forwarding, pickup
- Called, calling, connected party information
- Local three-way audio conferencing
- One-touch speed dial, redial
- Remote missed call notification
- Do not disturb function
- Electronic hook switch capable

Network and provisioning

- SIP Protocol Support
- SDP
- IETF SIP (RFC 3261 and companion RFCs)
- Two-port Ethernet switch 10/100Base-TX across LAN and PC Ports
- Manual or dynamic host configuration protocol (DHCP) network setup
- Time and date synchronization using SNTP
- Provisioning and call server redundancy supported
- QoS Support—IEEE 802.1p/Q tagging (VLAN), Layer 3 TOS, and DHCP
- VLAN—CDP, DHCP VLAN discovery, LLDP-MED for VLAN discovery
- Network Address Translation (NAT)—support for static configuration and “Keep-Alive” SIP signaling
- RTCP and RTP support
- Event logging
- Syslog
- Hardware diagnostics
- Status and statistics reporting
- TCP
- UDP
- DNS-SRV
- IPv4 and IPv6

Security

- 802.1X Authentication and EAPOL Media encryption via SRTP
- Transport Layer Security (TLS)
- Encrypted configuration files
- Digest authentication
- Password login
- Support for URL syntax with password for boot server address
- HTTPS secure provisioning
- Support for signed software executables

Power

- Built-in auto sensing IEEE 802.3af Power over Ethernet Class 2, 5.0 W (Max)
- External Universal AC/DC Adapter (optional) 5VDC @ 3A (15W)
- ENERGY STAR® rated

Approvals

- FCC Part 15 (CFR 47) Class B
- ICES-003 Class B
- EN55032 Class B
- CISPR32 Class B
- VCCI Class B
- EN55024
- EN61000-3-2; EN61000-3-3
- NZ Telepermit
- Korea KCC
- UAE TRA
- Russia CU
- Brazil ANATEL
- Australia RCM
- South Africa ICASA
- Saudi Arabia CITC
- China CCC
- RoHS Compliant

Safety

- UL 60950-1/62368-1
- CE Mark
- CAN/CSA C22.2 No 60950-1/62368-1-1
- EN 60950-1/62368-1
- IEC 60950-1/62368-1
- AS/NZS 60950-1

Operating conditions

- Temperature: 0 to 40°C (+32 to 104°F)
- Relative humidity: 5% to 95%, noncondensing

Storage temperature

- -40 to +70° C (-40 to +160° F)

Package contents

- VVX 150 console
- Handset with handset cord
- Network (LAN) cable—CAT-5E
- Power adapter

Size

- 24cm x 23cm x 5.7cm WxHxD
- 9.5in x 10in x 2.2in WxHxD

Weight

- Carton weight: 0.890kg (1.962 lbs)

Master carton quantity

- Ten (10)

For more information, please contact a sales representative. Visit ringcentral.com or call 855-774-2510.

RingCentral, Inc. (NYSE:RNG) is a leading provider of global enterprise cloud communications and collaboration solutions. More flexible and cost-effective than legacy on-premises systems, RingCentral empowers today's mobile and distributed workforce to communicate, collaborate, and connect from anywhere, on any device. RingCentral unifies voice, video, team messaging and collaboration, conferencing, online meetings, and integrated contact center solutions. RingCentral's open platform integrates with leading business apps and enables customers to easily customize business workflows. RingCentral is headquartered in Belmont, California, and has offices around the world.



RingCentral, Inc. 20 Davis Drive, Belmont, CA 94002. ringcentral.com

©2019 RingCentral, Inc. All rights reserved. RingCentral and the RingCentral logo are registered trademarks of RingCentral, Inc. Other third-party marks and logos displayed in this document are the trademarks of their respective owners.