

## Yealink SIP-T33G

Entry-level IP phone  
with color LCD



As an entry-level color screen IP phone with high performance, Yealink SIP-T33G supports one line and includes local five-way conferencing. With the extra-large 320 x 240-pixel color display, the SIP-T33G is not only stylish but also clearly visible. Designed with a new powerful chip, it greatly improves work efficiency. Additional features include a dual-port Gigabit Ethernet with integrated PoE, EHS35 support for Yealink wireless headsets, and an adjustable multi-angle stand support. Maximize productivity in both small and large office environments with this high-quality and cost-effective IP phone.



Unified firmware



Color screen



Elegant  
industrial design



Device  
management



HD audio



Opus



Five-way  
conferencing

## Key features and benefits

### Stronger performance, more possibilities

Equipped with a powerful chip, the T3 series has stronger computing power and more upgraded functions to ensure high productivity and a pleasant office experience. It's also flexible enough to meet different business demands.

### Superior HD audio, better communication

The Yealink T3 series provides distraction-free communications with industry-leading Smart Noise Filtering Technology, which delivers excellent sound quality without extraneous noises for easy-to-hear conversations.

### Yealink SIP-T33G

- Yealink HD Voice
- 2.4" 320 x 240-pixel color display with backlight
- Dual-port Gigabit Ethernet
- PoE support
- Opus codec support
- Local 5-way conferencing
- Support EHS wireless headset
- Unified firmware
- Support YDMP/YMCS
- Stand with 2 adjustable angles
- Wall mountable

## Specifications

### Audio features

- HD voice: HD handset, HD speaker
- Smart Noise Filtering
- Wideband codec: Opus, G.722
- Narrowband codec: G.711(A/μ), G.723.1, G.729, G.729A, G.726, iLBC
- DTMF: In-band, Out-of-band (RFC 2833) and SIP INFO
- Full-duplex hands-free speakerphone with AEC
- VAD, CNG, AEC, PLC, AJB, AGC

### Classic design, practical details

The T3 series inherits the design concept of the Yealink IP phone family. The advanced design includes a modern appearance and ergonomic details for a user-friendly experience.

### All-in-one platform, convenient management

Reduce your operations and management costs by deploying, managing, and troubleshooting your T3 series phones from the Yealink Device Management Platform.



### Phone features

- Call hold, mute, DND
- One-touch speed dial, hotline
- Call forward, call waiting, call transfer
- Group listening, SMS, emergency call
- Redial, call return, auto answer
- Local 5-way conferencing
- Direct IP call without SIP proxy

- Ring tone selection/import/delete
- Set date time manually or automatically
- Dial plan
- XML Browser, action URL/URI
- Integrated screenshots
- RTCP-XR, VQ-RTCPXR
- Enhanced DSS Key

### Directory

- Local phonebook up to 1,000 entries
- Black list
- XML/LDAP remote phonebook
- Smart dialing
- Phonebook search/import/export
- Call history: dialed/received/missed/forwarded

### IP-PBX features

- Busy Lamp Field (BLF), Bridged Line Appearance (BLA)
- Anonymous call, anonymous call rejection
- Hot-desking, voice mail
- Flexible seating
- Call park, call pickup
- Executive and Assistant
- Centralized call recording
- Visual voice mail
- Call recording

### Display and indicator

- 2.4" 320 x 240-pixel color display with backlight
- 16 bit depth color
- LED for call and message waiting indication
- Dual-color (red or green) illuminated LEDs for line status information
- Wallpaper
- Intuitive user interface with icons and soft keys
- Multilingual user interface

- Caller ID with name and number
- Screensaver
- Power saving

### Feature keys

- 4 line keys with LED
- 5 features keys: message, headset, redial, mute, hands-free speakerphone
- 6 navigation keys
- Volume control keys

### Interface

- Dual-port Gigabit Ethernet
- Power over Ethernet (IEEE 802.3af), class 2
- 1 x RJ9 (4P4C) handset port
- 1 x RJ9 (4P4C) headset port

### Other physical features

- Color: Classic Grey
- Wall mountable
- External Yealink AC adapter AC 100~240V input and DC 5V/600mA output
- Power consumption (PSU): 2-3W
- Power consumption (PoE): 3.5-5W
- Dimension (W\*D\*H\*T): 212mm\*186mm\*146mm\*42mm
- Operating humidity: 10~95%
- Operating temperature: -10~50°C (+14~122°F)

### Management

- Configuration: browser/phone/auto-provision
- Auto provision via FTP/TFTP/HTTP/HTTPS for mass deploy
- Auto-provision with PnP
- Zero-sp-touch, TR-069
- Phone lock for personal privacy protection
- Reset to factory, reboot
- Package tracing export, system log

