

Yealink T48S

Gigabit desk phone with seven-inch touchscreen display

The T48S IP Phone is a dynamic business communications solution for executives and professionals. It has 29 touch keys for moderate to high call volume and HD voice with OPUS support for superior sound quality. This phone offers a large touchscreen that makes switching between pages and applications swift, easy, and convenient.

The phone has USB port support for Wi-Fi and USB recording features.

The presence feature of this phone allows the user to monitor the in-use status of up to 27 other users. The intuitive user interface makes usability and navigation easy and requires minimal training.

Its two-port Gigabit Ethernet switch allows a single drop to the desktop for high-speed



Features and specifications

Touch keys

- Includes 29 touch keys with the ability to display the presence status for up to 27 users on the phone display

Display

- Seven-inch 800 x 480-pixel color touchscreen with backlight

Headset and hearing aid compatibility

- Dedicated RJ-9 headset port
- Hearing aid compatibility ITU-T P.370 and TIA 504A standards
- Compliant with ADA Section 508 Subpart B 1194.23 (all)
- Hearing aid compatible (HAC) handset for magnetic coupling to hearing aids
- Compatible with commercially-available TTY adapter equipment

Audio features

- HD voice technology delivers lifelike voice quality for each audio path—handset, the hands-free speakerphone, and the optional headset¹
- Frequency response—150 Hz–7 kHz for handset, optional headset, and hands-free speakerphone modes
- Codecs: G.711 (A-law and μ -law), G.729AB, OPUS (8kHz and 16kHz, G.722, G.722.1, iLBC)
- Individual volume settings with visual feedback for each audio path
- Voice activity detection
- Comfort noise generation
- DTMF tone generation (RFC 2833 and in-band)
- Low-delay audio packet transmission
- Adaptive jitter buffers
- Packet loss concealment
- Full-duplex hands-free speakerphone with AEC

Call handling features

- Busy lamp field (BLF)
- Distinctive incoming call treatment/call waiting
- LED for call and message waiting indication
- Call transfer, hold, divert (forward), pickup
- Called, calling, connected party information
- Local three-way audio conferencing
- One-touch speed dial, redial
- Remote missed call notification
- Do-not-disturb function
- Electronic hook switch capable
- Local configurable digit map/dial plan

Other features

- Adjustable base height

Interface

- Seven features keys: message, headset, hold, mute, transfer, redial, hands-free speakerphone
- Six navigation keys
- Volume control keys
- Illuminated mute key
- Illuminated headset key
- Illuminated hands-free speakerphone key

Protocol support

- IETF SIP (RFC 3261 and companion RFCs)

Network and provisioning

- SIP protocol support
- SDP
- IETF SIP (RFC 3261 and companion RFCs)
- Two-port Gigabit Ethernet switch
 - 10/100/1000 Base-TX across LAN and PC ports
 - Conforms to IEEE802.3-2005 (Clause 40) for physical media attachment
 - Conforms to IEEE802.3-2002 (Clause 28) for link partner auto-negotiation
- Manual or dynamic host configuration protocol (DHCP) network setup
- Time and date synchronization using SNTP
- FTP/TFTP/HTTP/HTTPS server-based central provisioning for mass deployments
- Provisioning and call server redundancy supported
- QoS support—IEEE 802.1p/Q tagging (VLAN), Layer 3 TOS, and DHCP
- VLAN-CDP, DHCP VLAN discovery, LLDP-MED for VLAN discovery
 - Network address translation (NAT) support for static configuration and “keep-alive” SIP signaling
- RTCP and RTP support
- Event logging
- Syslog

1. To enjoy all the benefits of HD voice when using the phone in the headset mode, you must use a wideband headset.

- Hardware diagnostics
- Status and statistics reporting
- IPv4
- TCP
- UDP
- DNS-SRV

Power

- Built-in auto sensing IEEE 802.3 at power over Ethernet (Class 2)
- External AC adapter, 100~240V input and DC 5V/2A output
- Power consumption (PSU): 2.2-4.9W
- Power consumption (PoE): 3.2-7.5W

Approvals

- FCC Part 15 (CFR 47) Class B
- ICES-003 Class B
- EN55022 Class B
- CISPR22 Class B
- VCCI Class B
- EN55024
- EN61000-3-2; EN61000-3-3
- NZ Telepermit
- UAE TRA
- Australia A & C Tick

Safety

- UL 60950-1
- CE Mark

- CAN/CSA-C22.2 No. 60950-1
- EN 60950-1
- IEC 60950-1
- AS/NZS 60950-1
- ICASA (add)
- CITC (add)

Operating conditions

- Temperature: +32 to 104°F (0 to 40°C)
- Relative humidity: 5% to 95%, noncondensing

Storage temperature

- -40 to +160°F (-40 to +70°C)

Package contents

- Yealink SIP-T48S IP Phone
- Handset with handset cord
- Ethernet cable (2m CAT5E UTP cable)
- Stand

Box dimensions/weight

- Qty/CTN: 5 PCS
- N.W/CTN: 8.2 kg
- G.W/CTN: 9.0 kg
- Giftbox size: 324mm*263mm*128mm
- Carton measure: 660mm*338mm*273mm

Country of origin

- China

For more information, please contact a sales representative. Visit ringcentral.com or call 855-774-2510.

RingCentral, Inc. (NYSE: RNG) is a leading provider of global enterprise cloud communications, collaboration, and contact center solutions. More flexible and cost-effective than legacy on-premises systems, RingCentral empowers modern mobile and distributed workforces to communicate, collaborate, and connect from any location, on any device, and via any mode. RingCentral provides unified voice, video meetings, team messaging, digital customer engagement, and integrated contact center solutions for enterprises globally. RingCentral's open platform integrates with leading business apps and enables customers to easily customize business workflows. RingCentral is headquartered in Belmont, California, and has offices around the world.